

405nm LASER SYSTEM—V12



- Features
- ◆ High output power of 12 W
 - ◆ 400 μ m/0.22NA multimode optical fiber
 - ◆ Center wavelength 400~405nm

- Applications
- ◆ LDI
 - ◆ Scientific research
 - ◆ Medical application

Typical Device Performance (20°C)

	Typical	Unit
Optical		
CW Output Power	12	W
Center Wavelength	400-405	nm
Fiber*		
Fiber Core Diameter	400	m
Fiber Length	2	m
Fiber Connector	SMA905	-
Electrical Parameter		
Voltage	DC24	V
Current	2.5	A
Electric Power	60	W
Power Supply & Control		
Control Model	Serial Port / Analog Voltage	
Power Regulation Range	0-12W	
Protection	Over Voltage/Over Current/Over Temperature	
Water cooling		
Refrigerating Capacity	60	W
Minimum Flow Rate	2.0	L/min
Water Pressure	0.3	MPa
Water Quality	RO/DI/DH2O	

* Customized fiber and connector available.

This instruction is for reference only. Han's TCS improves its products continually, therefore may change specifications without notice to customers, for details, please contact with Han's TCS sales.

@2022 Han's TianCheng Semiconductor Co., Ltd. All rights reserved.